





















invention is not limited by restrictive and rigid design guidelines, which is a limitation for monolithic mixer development. Repeatability Adequate High High Since most of the assembly is automated, with limited hand assembly, repeatability is excellent and comparable to monolithic manufacturing techniques. Customizability High Low High Low design cost, quick lead times, and the ability to make complex circuits make the invention ideal for custom requirements. Nonlinear Any vendor Many IC Choice limited Any Vendor Many In monolithic work, the designer is limited to using whichever Devices Choices by foundry Choices IC is offered by the foundry (usually a FET). In this invention, the designer can select from any device that will result in BEST achievable performance. Therefore performance will not be limited by nonlinear device, which is often the case in monolithic mixers. Substrate Duroid Semiconductor All thin-film Invention can be fabricated on a variety of materials giving Material (usually GaAs) compatible the designers an extra degree of freedom to tailor (Alumina, Quartz, performance. Invention also incorporates a metal-backed solid etc) substrate design, which is ideal for "chip and wire" and surface mount packaging. Most hybrid mixers use "suspended substrate" packaging, which is problematic.

The present invention has been described above in terms of a preferred embodiment and one or more alternative embodiments. Moreover, various aspects of the present invention have been described. One of ordinary skill in the art should not interpret the various aspects or embodiments as limiting in any way, but as exemplary. Clearly, other embodiments are well within the scope of the present invention. The scope of the present invention will instead be determined by the appended claims.

\* \* \* \* \*

