

## USPTO PATENT FULL-TEXT AND IMAGE DATABASE

[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Next List](#)[Bottom](#)[View Cart](#)*Searching US Patent Collection...***Results of Search in US Patent Collection db for:****AN/"Banner Engineering":** 73 patents.*Hits 1 through 50 out of 73*

Final 23 Hits

Jump To

Refine Search

AN/"Banner Engineering"

PAT. NO.	Title
1 <a href="#">11,002,634</a>	 <a href="#">Vibrational alarms facilitated by determination of motor on-off state in variable-duty multi-motor machines</a>
2 <a href="#">10,984,636</a>	 <a href="#">Modular indicator</a>
3 <a href="#">D904,986</a>	 <a href="#">Safety controller</a>
4 <a href="#">10,850,928</a>	 <a href="#">Conveyor sensor</a>
5 <a href="#">10,805,262</a>	 <a href="#">Modbus system having actual and virtual slave addresses and slave sensors</a>
6 <a href="#">10,783,758</a>	 <a href="#">Augmented sensing tower light assembly</a>
7 <a href="#">10,620,337</a>	 <a href="#">Retro-reflective sensor with multiple detectors</a>
8 <a href="#">10,566,148</a>	 <a href="#">Switch with circumferential indicator light</a>
9 <a href="#">10,475,299</a>	 <a href="#">Modular indicator</a>
10 <a href="#">10,459,113</a>	 <a href="#">User selectable remote programming for cascade-connected light curtains</a>
11 <a href="#">10,393,918</a>	 <a href="#">Retro-reflective sensor with multiple detectors</a>
12 <a href="#">10,373,451</a>	 <a href="#">Augmented sensing tower light assembly</a>
13 <a href="#">10,360,790</a>	 <a href="#">Safety touch button system having an intercommunications link</a>
14 <a href="#">10,347,092</a>	 <a href="#">Omni-directional in-line illumination indicator device</a>
15 <a href="#">10,253,954</a>	 <a href="#">Longitudinal stress mitigation for elongate LED luminaires</a>
16 <a href="#">10,234,547</a>	 <a href="#">Sensor with oblique-angle display</a>
17 <a href="#">10,045,407</a>	 <a href="#">Dual input voltage constant power indicator</a>
18 <a href="#">10,008,096</a>	 <a href="#">Light curtain protection system featuring a passive optical module</a>
19 <a href="#">9,997,031</a>	 <a href="#">Modular indicator</a>
20 <a href="#">9,985,414</a>	 <a href="#">Open-loop laser power-regulation</a>
21 <a href="#">9,984,835</a>	 <a href="#">Impact absorbing unitary cover assembly</a>
22 <a href="#">9,880,279</a>	 <a href="#">Object sensing using dynamic threshold hysteresis</a>
23 <a href="#">9,870,681</a>	 <a href="#">Field installable light curtain status module</a>

- |    |                           |   |
|----|---------------------------|---|
| 24 | <a href="#">9,768,572</a> |  <a href="#">Quick-connector conversion system for safety controller</a>  |
| 25 | <a href="#">9,761,113</a> |  <a href="#">Light curtain protection system featuring a passive optical module</a>  |
| 26 | <a href="#">9,753,178</a> |  <a href="#">Sensor component stabilization</a>  |
| 27 | <a href="#">9,671,523</a> |  <a href="#">Field installable light curtain status module</a>   |
| 28 | <a href="#">9,606,228</a> |  <a href="#">High-precision digital time-of-flight measurement with coarse delay elements</a>  |
| 29 | <a href="#">9,507,049</a> |  <a href="#">Object sensing using dynamic demodulation</a>   |
| 30 | <a href="#">9,466,213</a> |  <a href="#">Apparatus and method for power management of a system of indicator light devices</a>  |
| 31 | <a href="#">D768,013</a>  |  <a href="#">Sensor</a>  |
| 32 | <a href="#">9,286,804</a> |  <a href="#">Apparatus and method for power management of a system of indicator light devices</a>  |
| 33 | <a href="#">D748,506</a>  |  <a href="#">Sensor</a>  |
| 34 | <a href="#">D700,149</a>  |  <a href="#">Switch</a>  |
| 35 | <a href="#">D616,481</a>  |  <a href="#">Vision sensor</a>   |
| 36 | <a href="#">7,612,707</a> |  <a href="#">Configurable radar sensor</a>   |
| 37 | <a href="#">7,492,276</a> |  <a href="#">Micro-processor controlled indicator device</a>   |
| 38 | <a href="#">7,379,013</a> |  <a href="#">Detecting objects within a near-field of a frequency modulated continuous wave (FMCW) radar system</a>  |
| 39 | <a href="#">7,368,704</a> |  <a href="#">Self-contained fork sensor having a wide effective beam</a>   |
| 40 | <a href="#">D563,444</a>  |  <a href="#">Digital camera</a>  |
| 41 | <a href="#">7,329,854</a> |  <a href="#">System and method of connecting multiple safety light curtains</a>  |
| 42 | <a href="#">7,113,652</a> |  <a href="#">System and method for using normalized gray scale pattern find</a>  |
| 43 | <a href="#">D527,404</a>  |  <a href="#">Digital camera</a>  |
| 44 | <a href="#">7,095,893</a> |  <a href="#">System and method for determining an image decimation range for use in a machine vision system</a>  |
| 45 | <a href="#">7,085,433</a> |  <a href="#">System and method for performing rotational and translational testing for a reference image used in a normalized gray scale pattern find system</a>                   |
| 46 | <a href="#">6,946,643</a> |  <a href="#">Retro-reflective photoelectric sensor</a>  |
| 47 | <a href="#">6,808,389</a> |  <a href="#">Apparatus for igniting combustible fuel</a>   |
| 48 | <a href="#">6,778,079</a> |  <a href="#">Input/output methodology for control reliable interconnection of safety light curtains and other machine safety controls</a>  |
| 49 | <a href="#">6,593,755</a> |  <a href="#">Method and apparatus for detection sensor shielding</a>   |
| 50 | <a href="#">6,549,058</a> |  <a href="#">Signal processing circuits for multiplication or division of analog signals and optical triangulation distance measurement system and method incorporating same</a> |

[Help](#)